Surgic Pro2 QUICK OPERATION GUIDE

Control panel

NSK



Foot control



Preparation for Use



Insert the irrigation

Turn the pump cover counterclockwise 180°.



Insert the irrigation tube into a pack.



Connect the motor cord.



Connect the handpiece.



Attach the irrigation nozzle.





Attach the tube holders.

tube.

Starting operation



Turn on the power of Surgic Pro2 and each paired device.

The above is displayed.

The normal screen is displayed. Make sure that each device is connected.

NAKANISHI INC. 700 Shimohinata, Kanuma, Tochigi 322-8666, Japan

For details, see the operation manual.

The first step after purchase (Pairing with each device)



Press the ENTER Key.

▼ Foot control



This operation is not necessary when using Surgic Pro2 for the first time after purchase. If the foot control is unpaired or when using another foot control newly purchased, conduct the following operation. NOTICE : Paring can be done within 10 minutes after inserting the battery.



Press and hold the Left and Right buttons and the pedal at the same time.

PR



Connected

The control unit makes a beep and then "OK" will appear. Pairing is done. Make sure that the device is connected.



Press the CANCEL Key to return to the normal screen.

▼ Osseo 100+



Press the operating



Key.

Press the operating key to turn on the power. Press and hold the operating key.

"PA" is displayed.



The control unit makes a beep and then "OK" will appear. Pairing is done. Make sure that the device is connected.



Press the CANCEL Key to return to the normal screen.

▼ VarioSurg3





Turn on the power.

Connect the link cable beforehand.



Touch "Start".

When the LED turns blue, release the button.



The control unit makes a beep and then "OK" will appear. Pairing is done. Make sure that the device is connected. Also the LED of link module turns green.



×2



V External terminal





Launch the App.

Touch the icon.

Install the App beforehand.



www.nsk-dental.com/qr/app-surgicpro2

Press and hold the

button.



Enter the code "123456" and touch "Pair".



The control unit makes a beep and then "OK" will appear. Pairing is done. Make sure that the device is connected.

Press the CANCEL

×2

Press the CANCEL Key to return to the normal screen.

Issued Date: 2020.11.03 Printed Date: 2021.01.27 017